

IP-COM G1024D LAN 24-Port 10/100/1000M Base-T Ethernet ports (MDI/MDIX) Desk/rack mount(alt=TEG1024D



Šifra: 11711

Kategorija proizvoda: Mrežna oprema

Proizvođač: IP-COM

Cena: 10.770,00

Compliant with IEEE802.3, IEEE802.3u, IEEE802.3X, IEEE802.3ab standards

24*10/100/1000 Mbps auto-negotiation RJ45 ports

Auto MDI/MDIX

8000 MAC address and MAC auto Learning & Auto Aging

IEEE 802.3x full duplex flow control, and backpressure half duplex flow control

48 Gbps switching fabric for non-blocking line-speed forwarding

LED indicators for indicating working status and troubleshooting

Built-in power supply system with 6 kV common mode and 4 kV differential mode lightning protection

24 ports with 6 kV common mode lightning protection

IP camera connection

Plug and play

IP-COM G1024D is a 24-port gigabit unmanaged desktop/rack switch designed for video surveillance, offices, work groups, and SMEs for easy, economical and high-speed internet purposes. Its full duplex transmission rate can reach up to 2000 Mbps, ensuring the timely transfer of large files as well as smooth streaming videos. The professional integrated lightning protection circuit, the built-in power supply module, and all the 24 ports could withstand 6 kV lightning surge, ensuring the switch to run stably. G1024D is your ideal choice for extension, or upgrade to high-speed and stable gigabit optical network. Stable connection for 7*24

24*10/100/1000 Mbps auto-negotiation RJ45 ports, up to 2000 Mbps of full duplex transmission rate, line-speed forwarding by all ports, and large cache capacity ensure the timely transfer of large files and stable streaming video. Stay connected for 7*24.

Excellent lightning protection of ports

Professional integrated lightning protection circuit enables all the 24 ports to provide IV-class (6 kV in common mode) lightning protection, effectively decreasing the damage rate to the ports by lightning surge.

Professional lightning protection for power supply

The built-in power supply module is designed with enhanced lightning protection, which can withstand 6 kV lightning surge, 3 times higher than other ordinary switches, effectively protecting the switch from being damaged by adverse thunderstorm.

Innovative design

Full steel housing and plating through holes in three faces allow higher-efficient heat dissipation; fanless design ensures the noiselessness and dust free, harmoniously fitting into the offices; 13-inch size makes it mountable both on desktop and rack and plug and play function makes it easy for use.

Standard&Protocol IEEE 802.3?IEEE 802.3u?IEEE 802.3x?IEEE 802.3ab

Forwarding Speed

10Mbps : 14880pps

100Mbps : 148800pps

1000Mbps : 1488000pps
Transmission Media 10BASE-T: UTP category 3, 4, 5 cable
100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable
Port 24*10/100/1000Mbps auto-negotiation RJ 45 ports (Auto MDI/MDIX)
LED Indication 24* Link/Act indicator,1*power indicator
Dimensions 297mm×178mm×44mm
Switch Feature Store-and-Forward
MAC auto Learning & Auto Aging
8K MAC
48Gbps Backpanel bandwidth
Lighting Proof lightning protection 6KV for power supply,6KV for all ports
Power Input 100~240V AC,50/60Hz
Operating Environment Temperature:0?~45?
Humidity:10%~90% non-condensing
Storage Environment Temperature:-40?~70?
Humidity:5%~90% non-condensing
Tenda